JOLLY TOWER 6FT X 14FT (BACKLIT)





	-
A COLUMN AND A COLUMNA AND A	Contraction of Contra
	Contract of the local division of the local
	-t
1 1	
-++	
	-t
	1
	1
	the second secon
-	the second se
	A constant of the second se
	in the second se
	the second se
	- the second sec
	i contra da la c
	and an and a second sec
1	
and the second se	and the second se
And Personnel Name	
and the second se	

Product Description

The Jolly Tower is part of the Resort Extrusion family aluminum frames for Silicone-Edge Graphics (SEG). Custommade on the premises, Jolly Tower comes in varied sizes. Jolly Tower accepts four individual custom fabric graphics, excluding top and bottom. Insert graphics after frame is constructed by tilting it on its side. Transversely, push corners of graphic into the frame's recessed groove. Then, starting midway on the frame going toward the corners, continue pushing in the straight edges of the graphic. Repeat three times. Backlit option is available.

Display Dimensions	Graphic Size
--------------------	--------------

6' L x 6' W x 14' H

72' W x 168' H

Graphic Material

UV Backlit

Graphic Finishing

Silicone beading is sewn around the perimeter of the fabric graphic. Silicone beading is hidden from view once installed.

Display Construction

Aluminum Extrusion Frame

Ladder Lights Specification

Each Light Bead	.06843W
Angle	120°
Operating Voltage	12V
Total Wattage	350-600W MAX
Total Amperage	29A MAX

Transformer Specification

Output	12V/29A
Input	100-120VAC/7.0A
	200-240VAC/4.0A
	50/60Hz

Shipping Weights Shipping Dimensions

104 lbs (frame only) 112 lbs (with graphics) 40" | | ... 10") M ... 11 F" D

48" H x 18" W x 11.5" D

Graphic Turn Around Time

5-6 business days for up to 2 sets after proof approval

