Vector Frame:
Vector Frame Master Kit 16

Vector Frame Panel A
Total graphic area: 19.25"w X 98.375"h
Total visual area: 15.25"w X 94.375"h

Vector Frame Panel B
Total graphic area: 53.25"w X 98.375"h
Total visual area: 49.25"w X 94.375"h

Vector Frame Panel C and E
Total graphic area: 15.6875"w X 98.375"h
Total visual area: 11.6875"w X 94.375"h

Vector Frame Panel D
Total graphic area: 51.125"w X 98.375"h
Total visual area: 47.125"w X 94.375"h

Please be sure to include the 2" bleed around the perimeter of graphic panels. Do not design any critical elements (text, logos, etc.) within 2" of the edge (see dotted lines).

Please consider obstructions and spaces created by the extrusions when designing your graphics.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 100-120 ppi
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

PANEL A

MONITOR OBSTRUCTION

PANEL B

COUNTER OBSTRUCTION

PANEL C

PANEL WILL BE OBSTRUCTED BY HARDWARE
PANEL SHOULD ONLY BE SOLID COLOR OR PATTERN

PANEL D

bleed area
trim line
safe zone

PANEL E

PANEL WILL BE OBSTRUCTED BY HARDWARE
PANEL SHOULD ONLY BE SOLID COLOR OR PATTERN

Vector Frame:
Vector Frame Master Kit 16

Vector Frame Panel A
Total graphic area: 19.25"w X 98.375"h
Total visual area: 15.25"w X 94.375"h

Vector Frame Panel B
Total graphic area: 53.25"w X 98.375"h
Total visual area: 49.25"w X 94.375"h

Vector Frame Panel C and E
Total graphic area: 15.6875"w X 98.375"h
Total visual area: 11.6875"w X 94.375"h

Vector Frame Panel D
Total graphic area: 51.125"w X 98.375"h
Total visual area: 47.125"w X 94.375"h

Please be sure to include the 2" bleed around the perimeter of graphic panels. Do not design any critical elements (text, logos, etc.) within 2" of the edge (see dotted lines).

Please consider obstructions and spaces created by the extrusions when designing your graphics.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 100-120 ppi
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print



PANEL A


MONITOR
OBSTRUCTION
PANEL B
COUNTER
OBSTRUCTION

PANEL C

PANEL WILL BE OBSTRUCTED BY HARDWARE
PANEL SHOULD ONLY BE SOLID COLOR OR PATTERN

PANEL D

bleed area
trim line
safe zone

PANEL WILL BE OBSTRUCTED BY HARDWARE
PANEL SHOULD ONLY BE SOLID COLOR OR PATTERN

PANEL E